

Diamond Plate Technology®

The New Standard in Battery Power and Cycle Life.



U.S. Battery Manufacturing Company is proud to introduce its breakthrough technology! With "Diamond Plate Technology®" we are providing you with the highest rated batteries available today. Not only will they out perform the competition, they will last longer and provide you with improved charging profiles, saving both time and money. Don't wait any longer, power up with the **XC** Xtreme Capacity™ advantage today!



- XC ADVANTAGES:**
- X** Higher Peak Capacity
 - X** Increased Initial Capacity
 - X** Improved Energy Density
 - X** Enhanced Recharge-ability
 - X** Fortified Plate Construction
 - X** Improved Cycle Life



6 Volt
US 2000 XC

6 Volt
US 2200 XC

6 Volt
US 125 XC

6 Volt
US 145 XC

8 Volt
US 8VGC XC

8 Volt
US 8VGCHC XC

6 Volt
US AGM250 **NEW!**



1675 Sampson Ave.
Corona, CA 92879
(800) 695-0945

1895 Tobacco Road
Augusta, GA 30906
(800) 522-0945

717 North Belair Rd.
Evans, GA 30809
(888) 811-0945

www.USBATTERY.com



For The Longest Drive In Golf Always Demand U.S. Battery's *Diamond Plate Technology* Batteries

6 Volt Golf Car and Special Applications

Type	20 HR Rate	5 HR Rate	Min @ 75 Amps	Min @ 56 Amps	Min @ 25 Amps	Plates Cell	Length	Width	Height	Weight lbs.	Pallet QTY
US 1800 XC	208	157	107	N/A	392	14	10-1/4 (260)	7-1/8 (181)	11-1/4 (286)	56	48
US 2000 XC	216	172	114	N/A	445	15	10-1/4 (260)	7-1/8 (181)	11-1/4 (286)	59	48
US 2200 XC	232	181	122	N/A	474	19	10-1/4 (260)	7-1/8 (181)	11-1/4 (286)	63	48
US 125 XC	242	198	140	N/A	517	21	10-1/4 (260)	7-1/8 (181)	11-1/4 (286)	67	48
US 145 XC	251	216	154	N/A	562	19	10-1/4 (260)	7-1/8 (181)	11-7/8 (302)	70	48

8 & 12 Volt Golf Car and Special Applications

US 8VGC XC	170	138	90	128	337	15	10-1/4 (260)	7-1/8 (181)	11-1/4 (286)	64.5	48
US 8VGCE XC	121	101	60	90	222	11	10-1/4 (260)	7-1/8 (181)	11-1/8 (283)	55	48
US 8VGCHC XC	183	141	95	136	345	15	10-1/4 (260)	7-1/8 (181)	11-1/4 (286)	69	48
US 12V XC	155	122	77	110	292	13	13-1/8 (333)	7-1/16 (179)	11-3/8 (289)	90	36

12 Volt Starting Types

Type	CCA	CA @32 F.	5 HR Rate	Min @ 25 Amps	Plates/Cell	Length	Width	Height	Weight lbs.	Pallet QTY
24 - 60	525	660	N/A	85	12	10-1/4 (260)	7-13/16 (173)	9-1/8 (229)	37	72
24 - 50	420	475	N/A	70	9	10-1/4 (260)	7-13/16 (173)	9-1/8 (229)	34	72
26 - 50	450	560	N/A	60	10	8-3/16 (208)	6-13/16 (173)	8 (203)	28	90
70 - 60	450	560	N/A	60	10	8-3/16 (208)	7-1/16 (179)	7-3/4 (197)	28	90

6 Volt AGM

Type	20 HR Rate	5 HR Rate	Min of Discharge @75 Amps	Min of Discharge @56 Amps	Min of Discharge @25 Amps	CCA@ 0°F -18°C	CA@ 32°F 0°C	Length	Width	Height
US AGM 2000	210	185	120	182	450	710	855	10.24" (260mm)	7.09" (180mm)	10.79" (274mm)
US AGM 250	260	226	149	228	572	745	895	11.61" (295mm)	7.09" (180mm)	11.73" (298mm)

12 Volt AGM

US AGM 31	100	N/A	52	N/A	190	800	960	13.00" (330mm)	6.85" (174mm)	9.37" (238mm)
-----------	-----	-----	----	-----	-----	-----	-----	----------------	---------------	---------------

FEATURES:

- Diamond Plate Technology®** - Advanced paste formulation maximizes capacity life and recharge-ability.
- Antinium™** - This special grid metal mixture is used to reduce grid corrosion and water usage. In combination, these features will extend the life of your battery by 15-20%.
- Crystalock™** - Our advanced plate curing process insures structural strength and solid adhesion to the grid, the key to superior cycle life.
- SpeedCap™** - A positive locking cap that will not vibrate off or "spit" acid when removed. The "gang" feature allows for easy removal of all three caps at once saving time and money.
- Thicker Plates** - Our plates are the thickest in the business, assuring you the longest cycle life possible.
- Extra Electrolyte** - Using shorter, thicker plates allows for more electrolyte over the plates, extending required water intervals.
- Lifting Handle** - Makes installation and removal quick, easy and safe.

